



ELECTRICAL INDUSTRIES



2011 general catalogue 2012

FPB Palazzoli

MAESTRO THE PLUG-IN CEILING ROSE



MAESTRO THE PLUG-IN CEILING ROSE

TECHNICAL INFORMATION

- A decorative plug in ceiling rose of durable die cast construction, designed to allow the user to detach luminaires quickly & safely for cleaning, maintenance, or renewal
- Manufactured to comply with BS6972
- 6A 230VAC maximum rating
- Available in a choice of four finishes including polished brass/ polished chrome/ matt black / gloss white
- The fixed section of the ceiling rose incorporates IP2X shrouded & finger proof contacts, thus eliminating the possibility of exposed live contacts when the slide section is detached
- The slide section is equipped with a cord grip to prevent strain on the terminal connections
- Insulated parts are manufactured from flame retardant materials
- It is possible to support luminaires from the ceiling rose using two different methods.
 1. Extremely lightweight luminaires can be suspended by a circular flexible cord alone. A grommet is provided for this
 2. An open ended suspension hook is suitable for use with luminaires weighing no more than 5Kg
- Suspension hooks are connected to the slide section of the ceiling rose via a 12.5mm thread
- Captive screw type brass terminal blocks are provided for connections to permanent live, switched live, neutral, & earth, in similar format to a conventional ceiling rose.
- Each screw termination can accept 2x 1.5mmsq conductors
- Cable access knockouts are provided in the base plate, & are offset from centre to prevent the need to cut ceiling joists



FINISH	CEILING MAESTRO	
	BUBBLE PACK	BOXED
POLISHED BRASS	MC11A	MB11A
CHROME	MC11C	MB11C
MATT BLACK	MC11D	MB11D
GLOSS WHITE	MC11E	MB11E



Dealer's stamp



Argall Avenue, London E10 7QD - United Kingdom

UK Sales

Tel: +44 (0)20 8539 0237

Fax: +44 (0)20 8558 2718

e-mail: sales@lewden.co.uk

Export Sales

Tel: +44 (0)20 8988 7787

Fax: +44 (0)20 8558 2001

web: www.lewden.com